

XKPRD

Reader for pedestrian access control



Type of reader

passive proximity
keyboard

Installation

wall

- Available in 125 KHz and 13,56 MHz versions
- Also suitable for presence detection (in the double passive antenna version)
- Equipped with a graphic display for displaying date, time and personalized messages



TECHNICAL SPECIFICATIONS

Model	XKPRD 125	XKPRD 125 DA	XKPRD 1356
Enclosure		Plastic	
Operating ambient temperature		-10 ÷ +55°C	
Dimensions (LxDxH)		110x30x195 mm	
Connection		Bi-directional BUS (for connection to the Door Controller)	
Protection class		IP54	
Technology	125 KHz single antenna	125 KHz double antenna	13.56 MHz MIFARE, single antenna
Buzzer		Yes	
Keypad		Plastic capacitive 16-key keyboard with backlighting	
Display		3" graphic	
Installation type		wall	

FAMILY MODELS

Model	Description	Item code
XKPR 125D	Proximity 125 KHz + keyboard + display	103221
XKPR 125D DA	Double proximity 125 KHz + keyboard + display	103222
XKPR 1356D	Proximity 13.56 MHz, MIFARE + keyboard + display	105923

ELECTRONIC CONTROL UNITS



Door Controller LAN/
RS485

202323

ACCESSORIES



XKPRD reader adapter

401006



100 m skein of SPlnet
bus cable. Composed of
2 twisted pairs of 0.50
mm2

S-CAVO-BUS